

Trend - R



APPLICATIONS

- Railway
- Subways/Underground passages
- Prison
- Psychiatric Unit

CONSTRUCTION

- Fabricated sheet metal housing, fully welded construction, epoxy powder coated white
- Opal Polycarbonate diffuser 850° glow wire
- Stainless anti-tamper fixings

TECHNICAL DETAILS

- CRI>80
- CCT 4000K
- IK10+ Mechanical impact resistance
- Samsung LED's SDCM 3



OPTIONS

- /DALI - DALI dimming
- /M3 - 3hr Emergency
- /D3 - 3hr DALI monitored emergency
- /MW1 - Microwave sensor

DIMENSIONS

L, mm	W, mm	H, mm	D, mm	A, mm	A ₁ , mm	A ₂ , mm	B, mm
410	180	65	300	100			
690			450	175			
970			600	250	100	60	30
1250			900	400			
1530			1050	525			

PRODUCT CODE	DESCRIPTION
TRR/11/4K/WH	TREND R 11W 1,548LM 4K 410MM
TRR/19/4K/WH	TREND R 19W 2,334LM 4K 690MM
TRR/28/4K/WH	TREND R 28W 3,502LM 4K 970MM
TRR/38/4K/WH	TREND R 38W 4,668LM 4K 1250MM
TRR/41/4K/WH	TREND R 41W 5,295LM 4K 1530MM