

Trend - R



APPLICATIONS

- Railway
- Subways/Underground passages
- Prison
- Psychiatric Unit

CONSTRUCTION

- Fabricated sheet metal housing, fully welded construction, epoxy powder coated white
- Opal Polycarbonate diffuser 850° glow wire
- Stainless anti-tamper fixings

TECHNICAL DETAILS

- CRI>80
- CCT 4000K
- IK10+ Mechanical impact resistance
- Samsung LED's SDCM 3

DIMENSIONS

L, mm		W, mm	H, mm	D, mm	A, mm	A ₁ , mm	A ₂ , mm	B, mm
410	180	65	30	300	100	100	60	30
690				450	175			
970				600	250			
1250				900	400			
1530				1050	525			

PRODUCT CODE	DESCRIPTION
TRR/11/4K/WH	TREND R 11W 1,548LM 4K 410MM
TRR/19/4K/WH	TREND R 19W 2,334LM 4K 690MM
TRR/28/4K/WH	TREND R 28W 3,502LM 4K 970MM
TRR/38/4K/WH	TREND R 38W 4,668LM 4K 1250MM
TRR/41/4K/WH	TREND R 41W 5,295LM 4K 1530MM

OPTIONS	DESCRIPTION
/DALI	DALI Dimming
/M3	3Hr Emergency
/D3	3Hr DALI Monitored Emergency
/MW1	Microwave sensor

IP65

UK
CA

Ordering Format: Product Code / Option

Example: TRR/11/4K/WH/DALI