

Ventnor



APPLICATIONS

- Stores
- Car parks
- Food / Clean areas
- Warehouses
- Factories

CONSTRUCTION

- Extruded PMMA body
- Stainless Steel clips
- Opal diffuser
- IK10 rated impact test to BSEN 2262

TECHNICAL DETAILS

- Various Wattages
- CRI>80
- CCT 4000K
- Tridonic/Helvar Driver

DIMENSIONS

ORDER CODE	DESCRIPTION
VN/15/4K/65/OP	VENTNOR, 15W, 4K, 2,268LM, 662MM
VN/18/4K/65/OP	VENTNOR, 18W, 4K, 2,674LM, 662MM
VN/26/4K/65/OP	VENTNOR, 26W, 4K, 3,742LM, 1275MM
VN/36/4K/65/OP	VENTNOR, 36W, 4K, 5,348LM, 1275MM
VN/31/4K/65/OP	VENTNOR, 31W, 4K, 4,676LM, 1575MM
VN/45/4K/65/OP	VENTNOR, 45W, 4K, 6,685LM, 1575MM
VN/59/4K/65/OP	VENTNOR, 59W, 4K, 8,666LM, 1575MM

L, mm	W, mm	H, mm	D, mm	h, mm
662	96	111	350	100
	146			
1272	96		700	
	146			
1572	96		940	
	146			

OPTIONS	DESCRIPTION
/DALI	DALI ADDRESSABLE DIMMING
/M3	3HR EMERGENCY
/PIR	MOTION SENSOR
/MW1	MICROWAVE SENSOR
/DMW	DALI MICROWAVE SENSOR

Ordering Format: Product Code / Option

Example: VN/15/4K/65/OP/DALI

IP65

