



- Basic or DALI-2 Suspended Exit Sign
- White Polycarbonate Body
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP20 rated
- 30m Viewing Distance
- ISO 7010 Legends as Standard
- DDP (Deep Discharge Protection)
- Samsung LED's
- Supplied with a Kit of Legends
- Up to 1000mm Suspension
- Operates with LiteMesh Wireless Systems

A stylish and compact suspended Single/Double Sided LED Exit Sign that can be surface mounted.

The unit is available in either a Switchable Maintained/Non-Maintained, DALI-2 Self-Test, or a LiteMesh ready wireless version. The unit comes with a PMMA legend which offers an impressive 30m viewing distance.

The luminaire is supplied with a pack of inlay panels which includes Arrow Down (AD), Arrow Left (AL), Arrow Right (AR) and Arrow up (AU).

The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

Order Codes

STE/SM/M3	Switchable Maintained
STE/SM/DA	DALI-2 Type B, Switched Maintained, Non-Dimmable, or Self-Test M3/NM3
STE/SM/LMEM	LiteMesh Wireless Self-Test Switched Maintained/Non-Maintained

Technical Details:

	STE/SM/M3	STE/SM/DA
Mains Supply	230-240V AC 50/60 Hz	
Power Rating - Charging M-Mode*	5.7W 34mA $\lambda = 0.71$	5.4W 30mA $\lambda = 0.75$
Power Rating - Charged NM-Mode*	0.2W 11mA $\lambda = 0.07$	0.3W 8mA $\lambda = 0.15$
Duration	3-Hours	
Recharge Period	24-Hours	
Battery Size & Type	3.2V 3.8Ah LiFePO4 Cell	
Charge Current	225mA nominal	
Ingress Protection Rating	IP20	
Weight	1.2Kg	1.2Kg

* Following its initial charge, the unit will spend 90% of its operational life in standby mode