

A high-performance LED projector flood light with various wattages and beam angle options

- Feature
- Landscape
- Bridge illumination
- Statue
- Shrubbery





Features

- Chromate conversion coat die-cast aluminium body
- Super spot, spot, medium, wide, wide Flood beam angle available
- Ground mounting spike option
- Glass diffuser
- Double layer polyester powder coat resistant to corrosion and salt spray fog
- IP66
- IK08



Options

- Honeycomb louvre - (HCL)
- Visor – (VS)
- 12,20,30,40,60° (Beam Angle options)
- 2700K (27K) - 3000K (3K) – 4000K (4K)
- Custom paint finish – (RAL)
- Ground mounting spike – (GS)



Dimensions



Micro



Midi



Mini

Product Code

CEI-7-4K-GR-30	Centi Micro, 7w, 4K, 813.0lm, CRI>80, finished RAL7016
CEI-10-4K-GR-30	Centi Micro, 10w, 4K, 1,162.0lm, CRI>80, finished RAL7016
CEI-15-4K-GR-30	Centi Mini, 15w, 4K, 1,744.0lm, CRI>80, finished RAL7016
CEI-20-4K-GR-30	Centi Mini, 20w, 4K, 2,325.0lm, CRI>80, finished RAL7016
CEI-32-4K-GR-30	Centi Midi, 32w, 4K, 3,720.0lm, CRI>80, finished RAL7016
CEI-35-4K-GR-30	Centi Midi, 35w, 4K, 4,069.0lm, CRI>80, finished RAL7016
CEI-42-4K-GR-30	Centi Midi, 42w, 4K, 4,882.0lm, CRI>80, finished RAL7016

** Suffix 4K to required Kelvin **

** Suffix 30 for required beam angle option **

** Suffix end of code with accessory required**